

FEATURES



Anti-Static



Steel Toecap



Stainless Steel Midsole



Fuel Oil Resistant Outsole



Water Repellent Upper



Recycled Materials



SR Slip Resistance



Smaller Sizes

Product Details

Colour: Black
Size Range: UK 2-14
(INC 6.5 and 10.5)
Height: 3 inches
Weight: 580g



INDUSTRIES



Automotive and Aerospace



Cargo and Cruise Liners



Facility Management



Warehousing and Logistics

PRODUCT DESCRIPTION

PM102 Omaha safety footwear delivers trusted quality and lasting durability through a premium leather upper, steel toecap, stainless steel penetration resistant insert and dual density PU outsole. Engineered for warehouse, construction and manufacturing environments, it provides all day underfoot protection, superior grip and fatigue reducing comfort without compromise.

MATERIAL BREAKDOWN

UPPER MATERIAL: Water Repellent Coated Leather
EYELETS: Plastic
LACES: 100% Polyester
FOOTBED: EVA Foam, 100% Polyester Top Mesh
LINING: 100% Polyester Mesh
OUTSOLE: Dual Density PU
PROTECTIVE TOECAP: Steel
PROTECTIVE MIDSOLE: Activ-Step® Stainless Steel Penetration Resistant Insert

TECHNOLOGIES & ACCREDITATIONS

Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✓	✓	✓	✓	✗	✗	✓	✓
Class 2	✗	✗	✗	✗	✓	✓	✗	✗
200 Joules Toecap	✓	✓	✓	✓	✓	✓	✓	✓
Closed heel Area	✗	✓	✓	✓	✓	✓	✓	✓
Energy Absorption Of Seat Region	✗	✓	✓	✓	✓	✓	✓	✓
Anti-Static	✗	✓	✓	✓	✓	✓	✓	✓
Water Penetration And Absorption	✗	✗	✓	✓	✗	✗	✓	✓
Perforation Resistance To The Type	✗	✗	✗	✓	✗	✓	✗	✓
Cleated Outside	✗	✗	✗	✓	✗	✓	✗	✓
Water Resistance Of The Entire Shoe	✗	✗	✗	✗	✗	✗	✓	✓

EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undergone.

For further information contact the Rock Fall sales team.

Always check with your health and safety management if you are unsure of the appropriate specification required by your workplace.

Class 1 refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear
Class 2 Refers to all polymeric footwear including all rubber footwear.

S3, S5, S7 Specify metallic midsole tested at 1100N.

S3L, S5L, S7L specify non-metal midsole tested at 1100N with a 4.5mm nail.

S3S, S5S, S7S specify non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more information on specifications and standards, get in touch with our team for complete guide.

WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footwear is providing the correct arch support, and that your footwear is the correct size for your feet.

FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.

EU DECLARATION OF CONFORMITY

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

Rock Fall PM102 Omaha

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2022**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **CTC - 4, Rue Hermann Frenkel - 69367 Lyon, cedex 07, France. Notified Body 0075** who performed the Eu type examination (Module B) and issued the EU type -examination certificate:
0075/2599/161/04/25/0768

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body:

CTC - 4, Rue Hermann Frenkel - 69367 Lyon, cedex 07, France. Notified Body 0075.

Signature:

A handwritten signature in black ink, appearing to read "R. K. Wilson".

Position: Director

Date: 04/04/2025



Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsley Way
Alfreton
Derbyshire
DE55 4LS
UK

Approved Body: 0321

SATRA customer number: P1769

UKCA Type-Examination Certificate

Certificate number: AB0321/18795-01/E00-00

This UKCA Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation:
Following the UKCA Type-Examination this product group has been shown to satisfy the applicable essential health and safety requirements of the PPE Regulation (2016/425) as brought into UK law and amended as a Category II product.

Product reference:	Description:
ProMan PM100 Utah	Injection construction lace up ankle safety boot comprising black embossed microfibre upper with synthetic mesh linings. 8 D-rings comprise the laced fastening system with steel toecap MR604, steel metallic perforation insert MRA01 and with a black PVC outsole.
ProMan PM102 Omaha	Injection construction lace up low-cut safety shoe comprising black embossed microfibre upper with synthetic mesh linings. 8 eyelets comprise the laced fastening system with steel toe cap MR604, steel metallic perforation insert MRA01 and with a black PVC outsole.
ProMan PM103 Mars	Same as above but with a red PVC outsole and red linings.

Classification:
EN ISO 20345:2011 S3 SRC
Size : 35 – 49 EUR

Standards/Technical specifications applied:
EN ISO 20345: 2011

Technical reports/Approval documents:
INTERTEK: GZHT90981820, GZHT90989178, GZHT90989328, GZHT90892397, GZHT90887419

Signed on behalf of SATRA:

Pete Doughty

Date first issued: 04/10/2021
Date of issue: 04/10/2021
Expiry date: 04/10/2026



UKCA DECLARATION OF CONFORMITY

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM Declares that the PPE described hereafter;

ROCK FALL PM102 Omaha

Is in conformity with the provisions of PPE Regulation EU 2016/425, as brought into UK Law and amended, for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2011**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA Technology Centre Limited, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD United Kingdom. Approved Body 0321.** who performed the UKCA type examination (Module B) and issued the UKCA type -examination certificate: **AB0321/18795-01/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425, as brought into UK Law and amended, under the supervision of the notified body: **SATRA Technology Centre Limited, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD United Kingdom. Approved Body 0321**

Signature:

Position: Director

Date: 29/04/2021