Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

Style Ref.
RF605

Style Name.
Challenger

Specification: EN ISO 20345:2022 + A1:2024 S7S AN CI HI HRO LG SC FO SR + ASTM F2413-24 I/C PR

FEATURES

- Anti-Static
- Fibreglass Toecap
- PS Rated Penetration Resistant Insert
- Ladder Grip
- Non Metallic
- Ankle Protection
- Fuel Oil Resistant Outsole
- Heat Resistant Outsole to 300c
- Water Repellent Upper
- Fully Waterproof

INDUSTRIES

- Agricultural
- Airside
- Construction
- Emergency Services
- Highways
- House builders
- Offshore
- Quarry and Mining
- Rail
- Security

Product Details

Colour: Black
Size Range: UK 3 - 13
Height: 8.5 inches
Weight: 953g

PRODUCT DESCRIPTION

RF605 Challenger Unrivalled protection meets supreme comfort. Featuring BOA® Fit System for precision fit, premium water-repellent full-grain leather, fibreglass toecap, and waterproof construction. Activ-Step® anti-penetration insert and Cushion Pro footbed offer ultimate safety and support. Rugged outsole with scuff cap ensures superior traction in challenging terrains.

MATERIAL BREAKDOWN

UPPER MATERIAL: Leather Working Group Certified, Water Repellent Full Grain Leather
EYELETS: BOA® Eyestay Guard
LACES: BOA® Fit System
FOOTBED: Activ-Step® PU Foam, 100% Post Consumer Recycled Polyester Top Mesh
LINING: Waterproof Construction, 40% Nylon, 60% Post Consumer Recycled Polyester
OUTSOLE: PU Midsole, Nitrile Rubber
PROTECTIVE TOECAP: Fibreglass
PROTECTIVE MIDSOLE: Activ-Step® PS Rated Penetration Resistant Insert

TECHNOLOGIES & ACCREDITATIONS

activ step COMFORT FOOTBEDS

BOA® DIALED IN. PRECISION FIT.

More info on this style at:

WWW.ROCKFALL.COM/PRODUCTS/CHALLENGER

Tel. +44 (0) 1773 608616
Email. sales@rockfall.com

Rock Fall UK
Wimsey Way, Somercoates
Alfreton DE55 4LS
United Kingdom

Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

OVERVIEW OF SAFETY STANDARDS

Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✔	✔	✔	✔	✕	✕	✔	✔
Class 1	✕	✕	✕	✕	✔	✔	✕	✕
200 Joules Toecap	✔	✔	✔	✔	✔	✔	✔	✔
Closed heel Area	✕	✔	✔	✔	✔	✔	✔	✔
Energy Absorption Of Seat Region	✕	✔	✔	✔	✔	✔	✔	✔
Anti-Static	✕	✔	✔	✔	✔	✔	✔	✔
Water Penetration And Absorption	✕	✕	✔	✔	✕	✕	✔	✔
Perforation Reistance To The Type	✕	✕	✕	✔	✕	✔	✕	✔
Cleated Outside	✕	✕	✕	✔	✕	✔	✕	✔
Water Resistance Of The Entire Shoe	✕	✕	✕	✕	✕	✕	✔	✔

EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undercone.

For further infomation contact the Rock Fall sales team.

Always check with your health and safety managment if you are unsure of the appropriate specification required by your workplace.

Class 1 refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear
Class 2 Refers to all polymetric footwear including all rubber footwear.

S3, S5, S7 Specify metallic midsole tessted at 1100N.
S3L, S5L, S7L specifiy non-metal midsole tested at 1100N with a 4.5mm nail.
S3S, S55, S75 specifiy non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more infomation on specifications and standards, get in touch with our team for complete guide.

WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footbed is providing the correct arch support, and that your footwear is the correct size for your feet.

FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.

Tel. +44 (0) 1773 608616
Email. sales@rockfall.com

Rock Fall UK
Wimsey Way, Somercoates
Alfreton DE55 4LS
United Kingdom

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

DANAK
PROD Reg.No. 7035
Member of EA MLA

Danmark

EU-Type Examination Certificate

No. DK-PPE002239 i01

Holder of Certificate: **ROCK FALL UK LTD**
Major House, Wimsey Way, Alfreton Trading Estate
Alfreton, Derbyshire DE55 4LS
UNITED KINGDOM

Product: **Safety Footwear**
Model(s): **RF605 Challenger BOA Safety Boot**

Tested according to: EN ISO 20345:2022+A1:2024

Parameters:

Category:	II
Class of Protection:	S7S AN CI HI HRO LG SC FO SR
Size Range:	35-51
Toecap:	3160 Fiber Glass Toecap
Insert:	Aramid Fibre
Outsole:	3160 PU/RB
Construction:	Injection

The Certification Body of TÜV SÜD DANMARK ApS confirms that the listed product fulfils the applicable essential health and safety requirements with Annex V (Module B) of Regulation (EU) 2016/425 on personal protective equipment according to Article 19 (PPE of category II).
For details see: www.tuvsud.com/ps-cert

Evaluation report no.: DK-PPE002239 TRF i01
Valid until: 2031-03-16
Date, 2026-03-17

(Jamie Zhang)

This certificate has been issued in accordance with the TÜV SÜD Testing, Certification, Validation and Verification Regulations and constitutes the main page(s) of the combined Certificate and Annex.
The Conditions for the validity of this certificate are listed in the Annex.
For further details, related to this certification please contact babt@tuvsud.com

TÜV SÜD DANMARK ApS is Notified Body according to Regulation (EU) 2016/425 on personal protective equipment with the identification number 2443.

TÜV SÜD DANMARK ApS • Johanne Møllers Passage 1, 3. sal • 1799 Copenhagen V • Denmark

TÜV®

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

EU DECLARATION OF CONFORMITY

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ROCK FALL RF605 Challenger
Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2022+A1:2024**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **TUV SUD DANMARK ApS, Johanne Mollers Passage 1, 3, 1799 Copenhagen V Danmark. Notified Body 2443** who performed the Eu type examination (Module B) and issued the EU type examination certificate: **DK-PPE002239 i01**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body: **TUV SUD DANMARK ApS, Johanne Mollers Passage 1, 3, 1799 Copenhagen V Denmark. Notified Body 2443.**

Signature: Position: Director Date: 17/03/2026

Certificate of Conformance

Issued To : ROCK FALL UK

Our Reference No.: GZHT9139108402
Certificate Issue Date: Feb 05, 2026

Buyer's Name	--
Ref. No.	RF605
Brand	--
Manufacturer	--

We hereby declare that the product category (group) above has been tested by Intertek and meets the requirements of ASTM Specification ASTM F2413-24 as tested in accordance with ASTM Test Methods F2412-24 list the safety hazard(s) tested below.

Tests List:

Protective Toe Impact Resistance (I)
Protective Toe Compression Resistance (C)
Puncture Resistance Footwear (PR)

The test results are given in our report No. GZHT91391084, date Feb 05, 2026

Note:

1. This declaration applies to the particular sample tested and to the specific tests carried out as dated and detailed in the report(s) referenced above.

Approved By:
Intertek Testing Services Shenzhen
Limited, Guangzhou Branch

Guiliang Dong
Senior Lab Manager

Intertek Testing Services Shenzhen Limited, Guangzhou Branch
Room 401/501/601/701-1/801/901/1003, No. 8, East BaoYing Road
Huangpu District, Guangzhou 510730
深圳天祥质量技术服务有限公司广州分公司
广州市黄埔区保盈东路 8 号 401 房、501 房、601 房、701 房-1、801 房、901 房、1003 房
Tel: +86 020-28209114 Postcode:510730
www.intertek.com