Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

Style Ref.
**RF040**

Style Name.
**Manitoba**

**Specification:** EN ISO 20345:2022 + A1:2024 S3S CI HI FO HRO SC SR + ASTM F2413-24 I/C PR

## FEATURES

- Anti-Static
- Fibreglass Toecap
- PS Rated Penetration Resistant Insert
- Cold Insulation
- Fuel Oil Resistant Outsole
- Heat Insulation
- Heat Resistant Outsole to 300c
- Water Repellent Upper
- Recycled Materials
- Scuff Cap

## INDUSTRIES

- Agricultural
- Cold Temperature
- Offshore

## Product Details

Colour: Black
Size Range: UK 3 - 13
Height: 9.5 inches
Weight: 930g

## PRODUCT DESCRIPTION

RF040 Manitoba. Built for brutal cold, this rigger boot features 600g insulation and recycled faux fur lining rated to -30°C. A fibreglass toecap, Activ Step® penetration resistant insert, cushioned lite footbed, YKK side zip and nitrile rubber outsole deliver uncompromising protection and all day comfort.

## MATERIAL BREAKDOWN

**UPPER MATERIAL:** Leather Working Group Certified, Water Repellent Waxy Leather
**FOOTBED:** Activ-Step® 82% Pre-Consumer Recycled Foam, 100% Post Consumer Recycled Polyester Faux Fur
**LINING:** 100% Post Consumer Recycled Polyester 600g Thermal Faux Fur
**SCUFF CAP:** TPU
**OUTSOLE:** Nitrile Rubber
**PROTECTIVE TOECAP:** Fibreglass
**PROTECTIVE MIDSOLE:** Activ-Step® PS Rated Penetration Resistant Insert

## TECHNOLOGIES & ACCREDITATIONS

YKK
Little Parts. Big Difference.

**More info on this style at:**

**WWW.ROCKFALL.COM/PRODUCTS/MANITOBA**

Tel. +44 (0) 1773 608616
Email. sales@rockfall.com

Rock Fall UK
Wimsey Way, Somercoates
Alfreton DE55 4LS
United Kingdom

Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

# OVERVIEW OF SAFETY STANDARDS

| Category | SB | S1 | S2 | S3/L/S | S4 | S5/L/S | S6 | S7/L/S |
|---|---|---|---|---|---|---|---|---|
| Class 1 | ✔ | ✔ | ✔ | ✔ | ✕ | ✕ | ✔ | ✔ |
| Class 1 | ✕ | ✕ | ✕ | ✕ | ✔ | ✔ | ✕ | ✕ |
| 200 Joules Toecap | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ |
| Closed heel Area | ✕ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ |
| Energy Absorption Of Seat Region | ✕ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ |
| Anti-Static | ✕ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ |
| Water Penetration And Absorption | ✕ | ✕ | ✔ | ✔ | ✕ | ✕ | ✔ | ✔ |
| Perforation Reistance To The Type | ✕ | ✕ | ✕ | ✔ | ✕ | ✔ | ✕ | ✔ |
| Cleated Outside | ✕ | ✕ | ✕ | ✔ | ✕ | ✔ | ✕ | ✔ |
| Water Resistance Of The Entire Shoe | ✕ | ✕ | ✕ | ✕ | ✕ | ✕ | ✔ | ✔ |

## EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undercone.

For further infomation contact the Rock Fall sales team.

Always check with your health and safety managment if you are unsure of the appropriate specification required by your workplace.

**Class 1** refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear
**Class 2** Refers to all polymetric footwear including all rubber footwear.

**S3, S5, S7** Specify metallic midsole tessted at 1100N.
**S3L, S5L, S7L** specifiy non-metal midsole tested at 1100N with a 4.5mm nail.
**S3S, S55, S75** specifiy non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more infomation on specifications and standards, get in touch with our team for complete guide.

## WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footbed is providing the correct arch support, and that your footwear is the correct size for your feet.

## FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.



Tel. +44 (0) 1773 608616
Email. sales@rockfall.com

Rock Fall UK
Wimsey Way, Somercoates
Alfreton DE55 4LS
United Kingdom

Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
United Kingdom

Notified Body: 2777

SATRA customer number: P1769

# EU Type-Examination Certificate

## Certificate number: 2777/15449-02/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation. It has been issued Under Module B of Regulation 2016/425 on personal protective equipment. This product group has been shown to satisfy the applicable essential health and safety requirements as a Category II product.

| Product Ref: | Description: | |
|---|---|---|
| Rock Fall RF040 Manitoba | Design Type: | Half Knee Boot (Design C) |
| | Upper: | Black Crazy Horse Leather |
| | Tongue: | NA |
| | Collar: | Black Crazy Horse Leather |
| | Tongue Lining: | Brown Fur Lining |
| | Collar Lining: | Brown Fur Lining |
| | Vamp Lining: | Brown Fur Lining |
| | Quarter Lining: | Brown Fur Lining |
| | Counter Lining: | Brown Fur Lining |
| | Insole: | PEP-Composite |
| | Perforation Resistance: | Non-Metallic Perforation Resistance Insert Referenced PEP-Composite |
| | Toe Protection: | Non-Metallic Top Cap Referenced PEP-Composite |
| | Last Reference: | #PEP-PL |
| | Soling Construction: | Cemented |
| | Midsole Material: | N/A |
| | Outsole Material: | Black Rubber |
| | Sole Reference: | 2061#RB |
| | Insock/Footbed: | Brown Fur Lining + Green PU Full Removable Insock |
| | Fastening System: | Slip-on with Inner Quarter Zipper |
| | Scuff Cap: | Black TPU |
| | Heel Cap: | NA |
| | Size Range: | UK 3-13 |

**Classification:**
EN ISO 20345:2022+A1:2024 S3S HI CI FO HRO SC SR

Standards/Technical specifications applied:
EN ISO 20345:2022+A1:2024

Technical reports/Approval documents:
List of test reports in the approved technical file

Signed on behalf of SATRA: Kayleigh Aylward

**Date first issued: 14/12/2020**
**Date of issue: 02/10/2025**
**Expiry date: 02/10/2030**

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
**rockfall.com**

**EU DECLARATION OF CONFORMITY**

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM**

Declares that the PPE described hereafter;

**ROCK FALL RF040 Manitoba**
Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2022+A1:2024**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM**

Is identical to the PPE submitted to: **SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P. Republic of Ireland. Notified Body 2777.** who performed the Eu type examination (Module B) and issued the EU type -examination certificate: **2777/15449-02/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body:

**SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P. Republic of Ireland. Notified Body 2777.**

Signature: Position: Director Date: 14.10.2025

# Certificate of Conformance (COC)

*Certificate No. 2503037*

Issued by CTC Dongguan Co., Ltd., to the following model of PPE footwear:

**Company name: ROCK FALL UK LTD**

Product Description: OUTSOLE: 2061#, TOECAP: PEP-COMPOSITE, MIDSOLE: PEP-COMPOSITE
Style name: RF040
Gender: Unisex (Tested size US9)

| Picture of footwear & outsole | Picture of non-metal puncture resistance insert |
|---|---|
| |  |

This product meets the performance requirements of ASTM Specification F2413-24 as tested in accordance with ASTM Test Methods F2412-24 for the following safety hazards:

| Safety hazards | CTC testing report No. | Issued date of report |
|---|---|---|
| 5.2 Impact Resistant (I) | D250305183_1 | 14 March, 2025 |
| 5.3 Compression Resistant (C) | D250305183_1 | 14 March, 2025 |
| 5.8 Puncture Resistant (PR)<br>5.8.7 Determination of puncture force<br>5.8.8 Determination of the flex resistance of puncture-resistant insert | D241236354_1 | 30 December, 2024 |

Note :
1. This declaration applies to the particular sample tested and to the specific tests carried out as dated and detailed in the report(s) referenced above.
2. This certificate is valid only for the applicant's selected test items and must not be used without the attached test report(s).

Issue date of certificate:
March 19, 2025

Issued in Dongguan by:
Kevin LEE
PPE Manager of CTC Greater China

**CTC Dongguan Co., Ltd.**
1 Floor, No.14 building, Small and Medium sized Enterprises Pioneer Park,
SSL Industry Park, Dongguan - P.R. CHINA
Tél. : +86 769 23 03 77 70 Fax : +86 769 23 03 77 71
E-mail : ctcdongguan@ctcgroupe.com